



CONSOLE INVERTER

18000 BTU/H 24000 BTU/H 36000 BTU/H
48000 BTU/H 60000 BTU/H



Model	ML-CEI-H18A4/R1N	ML-CEI-H24A4/R1N	ML-CEI-H36A4/R1N	ML-CEI-H48A4/R1N	ML-CEI-H60A4/R1N
Performance	18000BTU/Hr	24000BTU/Hr	36000BTU/Hr	48000BTU/Hr	60000BTU/Hr
Classe énergétique Froid / Chaud	A++	A++	A++	A++	A++
Alimentation électrique (V/Ph/Hz)	220-240V-1-50Hz	220-240V-1-50Hz	380 - 415V-3-50Hz	380 - 415V-3-50Hz	380 - 415V-3-50Hz
Puissance frigorifique (Btu/h)	18000 (5220-19100)	24000 (7400-28000)	36000 (9900~41000)	48000 (14000-54600)	55000 (16400-59000)
Puissance frigorifique (kW)	5.00 (1.53-5.60)	7.00 (2.16-8.20)	10.5 (2.9~12.0)	14.00 (4.10-16.00)	16.00(4.80-17.30)
Puissance calorifique (Btu/h)	19100 (4800-21200)	27300 (6800-31800)	42650 (8900~41000)	55000 (15700-59700)	60000 (16700-63100)
Puissance calorifique (kW)	5.60 (1.40-6.20)	8.00 (1.98-9.30)	12.5 (2.6~13.2)	16.00 (4.60-17.50)	17.00 (4.90-18.50)
Puissance absorbée (kW)	1.62 (0.47-2.30)	2.18 (0.67-3.56)	3.28 (0.71~4.71)	4.95 (1.21-6.48)	5.71 (1.38-6.85)
Puissance calorifique nominale (kW)	1.47 (0.46-2.25)	1.91 (0.65-3.62)	3.64 (0.47~4.13)	4.57 (0.92-5.66)	4.96 (0.98-6.00)
Courant de refroidissement nominal (A)	7.11 (2.25-10.10)	9.57 (3.21-15.63)	14.56 (3.84~20.67)	7.76 (2.50-10.39)	8.97 (2.85-10.99)
Courant de chauffage nominal (A)	6.46 (2.20-9.88)	8.38 (3.11-15.90)	16.17 (2.57~18.3)	7.17 (1.90-9.08)	7.78 (2.02-9.62)
SEER W/W	7.0	6.9	6.9	6.9	6.9
COP W/W	4.1	4.2	4.3	4.4	4.4
Débit d'air intérieur (Hi / Mi / Lo) m3/h	900/730/650	1300/1052/920	1800/1550/1350	1900/1600/1400	1900/1600/1400
Niveau de bruit (Hi / Mi / Lo) dB(A)	43/40/34	43/40/34	46/43/38	50/47/41	51/48/42
Dimension(Wx DxH) net - Unite Interieur	930x660x205	1260x640x210	1620x650x220	1630x660x205	1630x660x205
Dimension (Wx DxH) d'emballage - Unite Interieur	650×650×290	1350x760x220	1720x730x220	910x910x350	910x910x350
Poids net (Kg)	32	33	35	45	50
Poids brut (Kg)	37	38	39	51	56
Poids net (Panel) (Kg)	3	5	5	5	5
Poids brut (Panel) (Kg)	5	7	7	7	7
Tuyau réfrigérant, côté liquide (mm)	6.35 (1/4")	9.52 (3.8")	9.52 (3.8")	9.52 (3.8")	9.52 (3.8")
Tuyau réfrigérant, côté Gaz (mm)	12.7 (1/2")	15.9 (5/8")	15.9 (5/8")	19 (3/4")	19 (3/4")
Longueur du tuyau maximum (m)	30	50	65	65	65
Denivele maximum (m)	20	25	30	30	30
Température de fonctionnement °C	16-32	16-32	16-32	16-32	16-32
Température ambiante Range (refroidissement / chauffage) °C	-10~52/-15~24	-10~52/-15~24	-10~52/-15~24	-10~52/-15~24	-10~52/-15~24
Dimension(WxDxH) net, EX (mm)	800x286x530	890x320x670	940x368x1366	940x368x1366	940x368x1366
Dimension(WxDxH) d'emballage, EX (mm)	920x400x620	1020x430x760	1080x460x1500	1080x460x1500	1080x460x1500
Poids net (Kg)	40	53	93	108	108
Poids brut (Kg)	44	58	103	116	116
Type de réfrigérant	R410A	R410A	R410A	R410A	R410A
Quantité (g)	1.28	1.90	2.85	3.70	3.70
Golden Fin	✓	✓	✓	✓	✓
Ventilateur Turbo	✓	✓	✓	✓	✓
Afficheur LCD	✓	✓	✓	✓	✓
Low Voltage	✓	✓	✓	✓	✓
Fresh Air	✓	✓	✓	✓	✓
Option Wifi	✗	✗	✗	✗	✗